




SPECIFICATIONS

MODEL : AUJ HP: _____
 VOLTS : _____ PHASE : _____

- * UL AND CANADIAN UL LISTED
- * HIGH STARTING TORQUE, CONTINUOUS DUTY MOTOR
- * MOTOR OVERLOAD PROTECTION
- * ELECTRO-MECHANICAL MODELS
 - * CLASS 2 (24 VOLT) CONTROL CIRCUIT
 - * IEC REVERSING CONTACTOR RATED 1-1/2 HP
- * SOLID STATE CONTROL MODELS (SUFFIX "S")
 - * CLASS 2 (24 VOLT) CONTROL CIRCUIT WITH ADVANCED SWITCH SELECTABLE FEATURES
- * HIGH AMP, INDUCTIVE LOAD RATED RELAYS
- * SOLENOID BRAKE
- * THREE BUTTON CONTROL: OPEN, CLOSE, STOP
- * WIRED TO ACCEPT REVERSING EDGE INPUT
- * HEAVY GAUGE, POWDER-COATED STEEL FRAME RAILS AND CONTROL BOX
- * ALL SPROCKETS AND PULLEYS PINNED OR KEYED, SOLID STEEL DRIVE SHAFTS
- * FULLY ADJUSTABLE FRICTION CLUTCH
- * HEAVY DUTY PILLOW BLOCK BEARINGS ON OUTPUT SHAFT
- * FLOOR LEVEL DISCONNECT FOR MANUAL OPERATION
- * FULLY ADJUSTABLE, INTERNAL, SHAFT DRIVEN LIMITS

TOLERANCE
 (EXCEPT AS NOTED)
 DECIMAL
 X.X ±0.030
 X.XX ±0.020
 X.XXX ±0.010



c.p. ALLSTAR CORPORATION
 PO Box 240
 Downingtown, PA 19335

FRACTIONAL ±1/32	APPROVED BY	SCALE 1:6	DRAWN BY TLS
ANGULAR ±1°	MATERIAL N/A	SHT 1 OF 1 © 1997	DATE 10/2/97
TITLE DWG, DIMENSIONS/SPECIFICATIONS, MODEL AUJ			DWG NO. 108035
			REV B