





WATCHMAN® EVO

W450

TELEPHONE ENTRY SYSTEM with **LIVE STREAMING VIDEO**



CELLGATE EXCLUSIVES



*Optional External Camera

- Pixel Activated Video
- All Video Stored on Camera
- Cloud-Stored Still Photos

NEW!

- Streaming Video Telephone Entry
- Verizon or AT&T Cellular Options
- **Plug-and-Play Internet** Option
- Optional External Camera*
- Microsoft Azure Hosted CellGate Cloud
- Custom, Real-Time Event Notifications
- Additional Wiegand/Camera Expansion Capability

EVO FEATURES

NEW!

NEW!

NEW!

- Calls Up to **9 Contacts**
- Includes Up to **3 Voice Numbers**
- Wiegand Functionality for Access Code Management
- Manage Up to **2 Gates or Doors**
- Maintains a Full-Time IP Cellular Connection
- Backlit LCD Display and Wiegand Keypad
- Open/Hold-Open and Picture Commands

cellgate

Experts in Cellular.
Innovators in Access Control.



cell-gate.com

855.694-2837

info@cell-gate.com

EVO Advantages

- Easy Activation
- Automated Email Workflows
- Convenient Call Group Management
- Manage Multiple Locations via CellGate Cloud
- Web-Based Management (desktop or mobile web)
- No Software Required
- Wiegand Time/Date Restrictions for Access Codes
- Open Gate on Demand

Dealer Benefits

- Easy 6-Wire Installation
- Pre-Configured System
- End-to-End Support
- Cellular Carrier and Signal Strength Verification
- Post-Installation Testing Credentials Provided

CellGate Cloud Benefits

- Web-Based Access
- Event Logs & Records with Pictures
- Create and Store Time/Date Restricted Access Codes
- Manage Notifications
- Custom Administrative Privileges
- Events Stored for 6 Months



Watchman EVO iOS/Android App

- Receive Audio and Video Calls from Visitors without Access Codes
- Live Video from Entrance
- Open Gate from App



 **cellgate**
Limited 2 Year Warranty

EVO Specifications

HD Camera angles:

Horizontal: 120°
Vertical: 64°

Power Consumption (12v DC):

Single Family: 700mA
External Cam: 350mA

1 – Wiegand input (26 bit)

2 Relays:

Contact rating: 0.5A @ 125vAC, 3A@30v DC
Switching voltage: 277v AC, 220v DC
Switching current: 4A

2 Digital inputs

IP65

Operating Temperature

-20°C - 55°C -4°F - 131°F

Cellular Technology/Networks

3G/LTE AT&T and Verizon
VoIP (no additional service required)
Full-time IP connection

Internet – plug and play VPN – no router configuration

Package

Dimensions 17.5 X 15.5 X 7.9 inches
Weight without external camera - 14lbs
Weight with external camera - 17lbs

Included in box

Watchman EVO
Power supply – 5A
Magnetic switch
Installation manual & user manual

Mounts available:

Pedestal (recessed mount ring and 2 bracket
mount antennas optional)
Surface mount (split electronics)
Flush mount (split electronics)

Antenna Options

L-bracket
Directional panel
Signal booster

support@cell-gate.com